

# METEORA



<b>Colours</b>	Aluminium
<b>Housing</b>	Black, White, Gold
<b>Inner ring colours</b>	Track light
<b>Fixture type</b>	Black, White, Gold
<b>Module</b>	Bridgelux V10 LED
<b>Driver</b>	Standard TRIAC-dimmable driver
<b>Light Output module</b>	1100lm
<b>CCT</b>	2700K
<b>CRI</b>	>90Ra
<b>Beam angles</b>	15°, 24°, 40°
<b>Adapter</b>	Powergear® 3-phase adapter included
<b>Rotatable</b>	350°
<b>Tilttable</b>	90°
<b>LED modules</b>	Standard
<b>Dimming Options</b>	TRIAC (standard), DALI, Casambi
<b>Options</b>	Lens (standard)
<b>Expected Lifetime</b>	>50.000h (L90/B50)
<b>Photobiological safety</b>	RG1 unlimited
<b>Power factor</b>	> 0.9
<b>UGR</b>	< 19
<b>Colour consistency</b>	3 SDCM
<b>Warranty</b>	3 years warranty on LED module and driver

Net Weight	Dimensions carton L x W x H	Qty outer carton
491 grams	8 x 7 x 24 cm	24

## Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Bridgelux V10 LED	1100lm	15W	73	927	>90						

### LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

<sup>1)</sup> Lumen output of LED module (COB)

<sup>2)</sup> Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

<sup>3)</sup> Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

