

METEORA-S



Colours	Aluminium
Housing	Track light
Fixture type	Bridgelux V6 LED
Module	Standard TRIAC-dimmable driver
Driver	500lm (DTW), 700lm
Light Output module	2700K, DTW (3000K-2000K)
CCT	>90Ra
CRI	15°, 24°, 40° (gold, black or white inner ring)
Beam angles	350°
Adapter	90°
Rotatable	Standard
Tilttable	TRIAC (standard), DALI, Casambi
LED modules	Lens (standard)
Dimming Options	>50.000h (L90/B50)
Options	RG1 unlimited
Expected Lifetime	> 0.9
Photobiological safety	< 19
Power factor	3 SDCM
UGR	3 years warranty on LED module and driver
Colour consistency	
Warranty	

Net Weight	Dimensions carton L x W x H	Qty outer carton
491 grams	8 x 7 x 24 cm	24

Available LED Modules

Description	Lumen	Watt	Lm/W	CCT	CRI	Description	Lumen	Watt	Lm/W	CCT	CRI
Bridgelux V6 LED	700lm	8W	73	927	>90						
Bridgelux V6 LED DTW	500lm	8W	73	3000K-2000K	>90						

LED modules

Standard: CRI>80 and >90 in CCT 2700K, 3000K, 4000K

Premium White (PW): for fresh white and depth of colour in retail environments

¹⁾ Lumen output of LED module (COB)

²⁾ Mentioned wattage applies for the COB only. Mentioned wattage applies for the most efficient CCT.

The power of the complete fixture will be slightly higher due to the power consumption of the driver.

³⁾ Values shown are average values and are subject to +/- 10% tolerance (set by international standards). The colour temperature is subject to a tolerance of up to +/- 150 Kelvin compared to the nominal value.

Technical data can be changed by Internova without prior notice.

