

# FOX ENERGY CUBE BATTERY STORAGE SYSTEM



## HIGH VOLTAGE BATTERY FROM FOX

The Energy cube is a high-performance, scalable battery storage system. The modular design allows for maximum flexibility, making it suitable for a broad range of storage applications.

Additional batteries can be installed in series, allowing for a maximum storage capacity of 28.21 kWh. Installation is easy, with a plug and play solution that can save valuable time for installers.

- 4.03 kWh Capacity
- Scalable to 28.21 kWh
- 90% Depth of Discharge
- Wide Temperature Tolerance
- Easy Installation
- CAN / RS485 Communication
- High Voltage



-  **High Voltage**
-  **Easy Installation**
-  **High Efficiency**
-  **Expandable System**
-  **90% DoD**

Model	ECS4100-H2	ECS4100-H3	ECS4100-H4	ECS4100-H5	ECS4100-H6	ECS4100-H7
<b>Electrical Characteristics</b>						
Battery Type	LiFePO4 Prismatic Cell					
Battery Module	1*CM4100	1*CM4100	1*CM4100	1*CM4100	1*CM4100	1*CM4100
	1*CS4100	2*CS4100	3*CS4100	4*CS4100	5*CS4100	6*CS4100
Nominal Capacity (Wh)	8060	12090	16120	20150	24180	28210
Nominal Voltage (V)	115.2	172.8	230.4	288	345.6	403.2
Operating Voltage (V)	97.2-131.4	145.8-197.1	194.4-262.8	243-328.5	291.6-394.2	340.2-459.9
Recommend Discharge Current (A)	25					
Max. Charge / Discharge Current (A)	50					
Peak Discharge Current (A)	60A @30sec					
Battery Pack Round-trip Efficiency	>95%					
Depth of Discharge	90%					
Cycle Life*1	≥6000					
Communication	CAN, RS485					
Display	CS: LED*1, CM: LED*7					
Scalability	Max. 7 Modules in Series					
<b>Operating Conditions</b>						
Installation Location	Outdoor / Indoor (Stand)					
Operating Temperature (°C)	-10 - 55					
Storage Temperature (°C)	-20 - 55					
Cooling method	Natural Convection					
Humidity	0% to 100% (No Condensing)					
Altitude (m)	Max. 2,000					
<b>Mechanical Characteristics</b>						
Dimensions (W*H*D) (mm)	570*350*380	570*470*380	570*590*380	570*710*380	570*830*380	570*950*380
Weight (kg)	68.5	103.3	138.1	172.9	207.7	242.5
<b>Certificates</b>						
Safety	IEC62619					
EMC	EN IEC 61000-6-1/2/3/4					
Transportation	UN38.3					
Ingress Protection	IP65					

\*1 25°C, @90% DOD, 0.2C charging/discharging

\*2 Refer to FoxESS Battery Warranty Terms and Conditions

