



Model No.: QL-F5050X30-CX4-12/24
 LED Q'ty: 60LEDs/m
 PCB Dimension: 500*12*0.22mm
 Voltage: DC12V, DC24V
 Power Consumption: 19.2W/m
 Waterproof Grade: IP20-IP67
 With Four Chips in One LED

Specifications:

Model No.	Color	LED Qty	λ (nm)/(CT:K)	Luminous Flux	PCB Dimensions (mm)	Work Voltage	Power	Water proof	Packing	
QL-F5050A30-CP4-12/24	RGB Pure White	60/m	■: 620-630 ■: 465-470 ■: 520-525 ■: 590-595 □: 6000-6500K □: 4000-4500K □: 3000-3500K	■: 100-120 ■: 90-110 ■: 250-270 ■: 100-120 □: 350-390 □: 340-360 □: 300-330	500*12*0.22	DC12V DC24V	19.2W/m	No	5m/reel	
QL-F5050A30-CN4-12/24	RGB Nature White									No
QL-F5050A30-CW4-12/24	RGB Warm White									
QL-F5050A30-CY4-12/24	RGB Amber									
QL-F5050C30-CP4-12/24	RGB Pure White	60/m						IP67		
QL-F5050C30-CN4-12/24	RGB Nature White									
QL-F5050C30-CW4-12/24	RGB Warm White									
QL-F5050C30-CY4-12/24	RGB Amber									

Features:

1. Input voltage: DC 12V, DC24V
2. Super bright top SMD 5050 LED as lighting sources
3. Different colors are available
4. Every 3-LED are cuttable for 12V strips, 6LEDs are cuttable for DC24V
5. White, Black, Yellow PCB Board are available
6. With 3M adhesive tape on backside