

PULSAR MAX Technical Datasheet

General Specifications

Model	Pulsar Max
Colour	Black
Cable Length	5 m (7 m optional) ^[1]
Charging Mode (IEC 61851-1)	Mode 3
Dimensions	198x201x99 mm (without cable)
Weight	1.3 kg (without cable)
Operating Temperature	-25 °C to 40 °C
Storage Temperature	-40 °C to 70 °C
Standards	IEC 61851-1, IEC 61851-21, IEC 62196, Low Voltage Directive 2014/35/EU, EMC Directive 2014/30/EU, RED Directive 2014/53/EU, WEEE Directive 2012/19/EU, RoHS Directive 2011/65, BS 7671:2018+A1:2020


User Interface & Communications

Connectivity	Wi-Fi, Bluetooth
User Identification	myWallbox App & Portal
User Interface	myWallbox App & Portal ^[2]
Charger Status Information	Halo RGB LED, myWallbox App & Portal
Included Features	Power Sharing Smart
Optional Features	Power Boost Dynamic Power Sharing Eco-Smart

Electrical Specifications

Charging Power	7,4 kW	11 kW	22 kW
Rated Voltage AC ± 10%	220-240 V	380-400 V	380-400 V
Rated Current	32 A (1P)	16 A (3P)	32 A (3P)
Connector Type (IEC 62196-2)	Type 1 / Type 2	Type 2	Type 2
Cable Width	up to 13 mm ²	up to 13 mm ²	up to 13 mm ²
Configurable Current	from 6 A to rated current		
Rated Frequency	50 Hz / 60 Hz		
Protection Rating	IP54 / IK10		
Surge Category	CAT III		
Residual Current Detection	DC 6 mA		
RCCB	External RCCB Type A required		

Dimensions



Part Number Structure

W **A** **B** **D** **F** **C** **E**
Wallbox Chargers S.L. Made in Spain
 Carre del Foc 68, 08038 Barcelona, Spain 08/2020
 SN: 12345678 UID: ABCDEFGH
 PN: XXXX-X-X-X-XXX REV X Charger family
 -25°C to 40°C
 Outdoor use IP54
 Input/Output:
 230/400VAC, 50Hz,
 32A (@25°C) XP+N+PE

	Code	Definition
A Model	PLP2	Pulsar Max
B Cable	0	5 m
	M	7 m
C Connector	1	Type 1
	2	Type 2
D Power	2	7,4 kW
	3	11 kW
	4	22 kW
E Additional Feature	9	Residual Current Detection (DC 6 mA)
	F	Residual Current Detection (DC 6 mA) + Earthing protection
F Custom	XX1	Black

[1] Only available for Type 2 connectors.
[2] OCPP compatible.